

Kabeltabelle
Cable table

KAB 01

9012.0374 / 20.07.2021

Positionierer/ positioner	Motor Typ/ Motor type	Passende OWIS-Steuerung/ suitable OWIS controller	Motorkabel/ motor cable
MTM 60/120 LTM 45/60/80/120	SM	PS 10-32/PS 30/PS 35/PS 90+	53.20.S300
	DC		53.20.D301
LPTM 30/ LIMES 64N/84N/124N	SM	PS 10-32/PS 30/PS 35/PS 90+	53.20.D301
	DC		
LIMES 150	SM	PS 10-32/PS 30/PS 35/PS 90+	53.20.S300
	DC		53.20.D301
LIMES 64N/84N/124N/150-IMS	SM	PS 30	53.20.D3019
		PS 90+	53.20.D301
	DC	PS 30/PS 35/PS 90+	53.20.D301
LIMES 170-(IMS)	SM	PS 90+	53.27.D305
	DC		53.27.D304
PKTM 50/70/130/190 CROSS 50/70/130/190	SM	PS 10-32/PS 30/PS 35/PS 90+	2x 53.20.S300
	DC		2x 53.20.D301
HVM 60N/HVM 100N	SM	PS 10-32/PS 30/PS 35/PS 90+	53.20.D301
	DC		
HUMES 60/100/150	SM	PS 10-32/PS 30/PS 35/PS 90+	53.20.S300
	DC		53.20.D301
HUMES 200	SM	PS 10-32/PS 30/PS 35/PS 90+	53.20.S300
	DC	PS 90+	53.20.D301
HUMES 60/100/150-IMS	SM	PS 30	53.20.S300 + 53.20.M300
		PS 90+	53.20.S300H
	DC	PS 30/PS 35/PS 90+	53.20.D301M
HUMES 200-IMS	SM	PS 30	53.20.S300 + 53.20.M300
		PS 90+	53.20.S300H
	DC	PS 90+	53.20.D301M
DRTM 40/65/90 DMT 40/65/100/130N	SM	PS 10-32/PS 30/PS 35/PS 90+	53.20.S300
	DC		53.20.D301
DMT 200N-(IMS)	SM	PS 90+	53.27.D305
	DC		53.27.D304
MOGO 40/65/150	SM	PS 10-32/PS 30/PS 35/PS 90+	53.20.D301
	DC		
TPM 150	SM	PS 10-32/PS 30/PS 35/PS 90+	2x 53.20.D301
	DC		
IBM 65 FRM 40/65 MMS 19	SM	PS 10-32/PS 30/PS 35/PS 90+	53.20.S300
	DC		53.20.D301

Technische Daten/Technical Data KAB-09 (53.20.xxxx) &KAB-79 (53.27.xxxx)

		KAB-09	KAB-79	
Außendurchmesser	Outer diameter	8,00 (± 0,25)	16,30 (± 0,40) x 8 (± 0,25)	mm
Biegeradius ruhend	Bending radius static	7,5	7	x Außendurchmesser / outer diameter
Biegeradius dynamisch	Bending radius dynamic	10	10	x Außendurchmesser / outer diameter
Außenmantel	Outer material	PUR		
Schirm	Shielding	Doppelt geschirmt / double shielded		
Aderisolation	Wire isolation	TPE halogenfrei / halogen free		
Temperaturbereich	Temperature	- 40 bis/up to + 90		° C