

**Kabeltabelle**  
**Cable table**

**KAB 01**

9012.0374 / 20.07.2021

Positionierer/ positioner	Motor Typ/ Motor type	Passende OWIS-Steuerung/ suitable OWIS controller	Motorkabel/ motor cable
MTM 60/120 LTM 45/60/80/120	SM DC	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.S300</a> <a href="#">53.20.D301</a>
LPTM 30/ LIMES 64N/84N/124N	SM DC	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.D301</a>
LIMES 150	SM DC	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.S300</a> <a href="#">53.20.D301</a>
LIMES 64N/84N/124N/150-IMS	SM	PS 30	<a href="#">53.20.D3019</a>
	SM	PS 90+	<a href="#">53.20.D301</a>
	DC	PS 30/PS 35/PS 90+	<a href="#">53.20.D301</a>
LIMES 170-(IMS)	SM	PS 90+	<a href="#">53.27.D305</a>
	DC	PS 90+	<a href="#">53.27.D304</a>
PKTM 50/70/130/190 CROSS 50/70/130/190	SM	PS 10-32/PS 30/PS 35/PS 90+	2x <a href="#">53.20.S300</a>
	DC	PS 10-32/PS 30/PS 35/PS 90+	2x <a href="#">53.20.D301</a>
HVM 60N/HVM 100N	SM	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.D301</a>
	DC	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.D301</a>
HUMES 60/100/150	SM	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.S300</a>
	DC	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.D301</a>
HUMES 200	SM	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.S300</a>
	DC	PS 90+	<a href="#">53.20.D301</a>
HUMES 60/100/150-IMS	SM	PS 30	<a href="#">53.20.S300</a> + <a href="#">53.20.M300</a>
	SM	PS 90+	<a href="#">53.20.S300H</a>
	DC	PS 30/PS 35/PS 90+	<a href="#">53.20.D301M</a>
HUMES 200-IMS	SM	PS 30	<a href="#">53.20.S300</a> + <a href="#">53.20.M300</a>
	SM	PS 90+	<a href="#">53.20.S300H</a>
	DC	PS 90+	<a href="#">53.20.D301M</a>
DRTM 40/65/90 DMT 40/65/100/130N	SM	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.S300</a>
	DC	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.D301</a>
DMT 100-IMS	SM	PS 30	<a href="#">53.20.D3019</a>
	SM	PS 90+	<a href="#">53.20.D301</a>
	DC	PS 30/PS 35/PS 90+	<a href="#">53.20.D301</a>
DMT 200N-(IMS)	SM	PS 90+	<a href="#">53.27.D305</a>
	DC	PS 90+	<a href="#">53.27.D304</a>
MOGO 40/65/150	SM	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.D301</a>
	DC	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.D301</a>
TPM 150	SM	PS 10-32/PS 30/PS 35/PS 90+	2x <a href="#">53.20.D301</a>
	DC	PS 10-32/PS 30/PS 35/PS 90+	2x <a href="#">53.20.D301</a>
IBM 65 FRM 40/65 MMS 19	SM	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.S300</a>
	SM	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.S300</a>
	DC	PS 10-32/PS 30/PS 35/PS 90+	<a href="#">53.20.D301</a>

**Technische Daten/Technical Data KAB-09 (53.20.xxxx) &KAB-79 (53.27.xxxx)**

		KAB-09	KAB-79	
Außendurchmesser	Outer diameter	8,00 (± 0,25)	16,30 (± 0,40) x 8 (± 0,25)	mm
Biegeradius ruhend	Bending radius static	7,5	7	x Außendurchmesser / outer diameter
Biegeradius dynamisch	Bending radius dynamic	10	10	x Außendurchmesser / outer diameter
Außenmantel	Outer material	PUR		
Schirm	Shielding	Doppelt geschirmt / double shielded		
Aderisolation	Wire isolation	TPE halogenfrei / halogen free		
Temperaturbereich	Temperature	- 40 bis/up to + 90		° C